



Blood Bank Processing Solutions

DP-2065R PLUS



ISO Quality 9001/13485
ANMAT: PM1532-1

📍 Calle 34 (Ex Francia) N° 3917, San Martín - B1650IHM - Bs. As. - Arg.
☎ 4755-7780 / 4755-4004 📞 11 2488 7703
🌐 www.presvac.net ✉ presvac@presvac.net





The **Presvac refrigerated centrifuge**, model **DP-2065 R PLUS**, is a **high-capacity system** designed for **intensive processing** in **blood banks and transfusion centers**. Its rotor accommodates up to **6 blood bags** (double, triple, or quadruple configurations) using **1,000 mL bag carriers**, and reaches a **maximum speed of 3,500 RPM**, ensuring efficient and reliable component separation.

The **MEMOSOFT V** control system allows **programming of up to 50 different protocols**, with precise adjustment of **speed, temperature, time, acceleration, and braking**.

The centrifuge incorporates **multiple safety systems**, including lid locking, imbalance detection with immediate shutdown and audible and visual alarms, a brushless low-maintenance induction motor, and a CFC-free refrigeration system, environmentally friendly.

Optional accessory: **barcode reader with PC connection via RS-232 cable**. It allows the software to record the date, time, method, and duration of each centrifugation cycle, ensuring process traceability.

Advanced Safety Features



Imbalance detection with immediate stop

Provides real-time imbalance monitoring with an instant stop function, protecting both the equipment and samples against any load imbalance.



Anti-vibration lid lock

Prevents accidental opening during operation, safeguarding sample integrity and operator safety.



Comprehensive alarm system

Equipped with a multifunction alarm system that monitors abnormal voltage, high temperature, over-speed, load imbalance, missing rotor, brake anomalies, and motor faults.



High-quality connectivity

Equipped with a 220 V, 50/60 Hz power connector for easy, fast, and safe operation.



Robust construction

Steel sheet structure with epoxy paint and a stainless-steel chamber that provides durability and safety.



All-stainless-steel chamber and inner lid

Delivers excellent durability and corrosion resistance, ensuring a long service life.



Emergency lid release

Allows the lid to be manually opened in the event of an emergency or power loss.



Key features of the 6-bag centrifuge

- **Expanded programming capacity**

Streamline operations with built-in memory that stores 50+ customized programs—ideal for standardizing and automating complex procedures in high-demand environments.

- **Advanced thermal efficiency**

Reach a rapid working temperature from ambient conditions, ensuring fast start-up and efficiency in the preparation of temperature-sensitive processes.

- **Low-impact acoustic design**

Reduce laboratory noise with an optimized structural design that keeps sound levels below 65 dB, even at maximum speed.

- **Dynamic cycle management**

Fine-tune every operational stage with 10 programmable acceleration and deceleration ramps, allowing centrifugation profiles to be tailored to the specific requirements of each application.

- **High-efficiency, low-maintenance drive system**

Powered by a brushless induction motor, this unit delivers clean, continuous operation with minimal maintenance, supporting long-term operational reliability.

- **Enhanced stability**

A low center-of-gravity structural design provides maximum mechanical stability during operation, contributing to safe, consistent, and reproducible results across all load types.





MEMOSOFT V Control Panel



The **MEMOSOFT V control panel** combines proven reliability and safety with an intuitive **user communication system** via **graphic displays** for streamlined programming and equipment management. This upgraded platform can **automatically store all processed units**, ensuring maximum traceability throughout blood unit processing.

With this management system, you can identify **exactly when each blood unit was processed** and securely store the complete centrifugation cycle data—**date, time, method, and process duration**—delivering a **comprehensive, traceable, and secure** record.





Program Display & Activation



Program Selection




Program Creation & Storage



Delete Program



Manual



PC Data Connection & Transfer



User Group



Enable Data Storage System



Date & Time Settings



Delete Database



Maintenance Time



Centrifugation Time



User Screen Lock



User Identification

Display Graphics Description

```
NAME : P001
TIMER : 13:00
SPEED : 2800 rpm
TEMP. : 22.0 °C
ACCEL. : 75
DECEL. : 75 Actual
CURVE : 10
ROTOR : 35 cm
```

Manual Program Creation

Real-Time Parameter
Display During Operation

```
TIME : 13:00
TEMP. °C : 22.0
SPEED : 2800 RPM
RCF : 3070 xg
```



Technical Data Sheet – Model DP-2065R PLUS

Technical Specifications	Value
Depth	880 mm
Length	730 mm
Height	1010 mm
Weight	207 kg
Materials	Ext: Enameled steel / Int: Stainless steel
Maintenance clearance	Does not require leveling due to castor wheels
Mounting	Horizontal wheels with brakes
Max. electrical current draw	15 A (11 A in continuous operation)
Max. power	3300 VA
Power supply	220 V \pm 3%, 50/60 Hz
Heat dissipation	2500 kcal/h max. per cycle
Required ambient temperature	25 °C
Refrigerant	R404a
Working pressure	50 psi suction pressure
Warranty	1 year
Scheduled maintenance (per manufacturer)	6 months
Certifications	ISO 9001 ISO 13485 ANMAT

Technical specifications – 6B swinging rotor (6 bags)

Technical Specifications	Value
Material	Steel and aluminum alloy
Processing capacity	6 blood bag holders
Tube volume	1000 mL
Maximum speed	3,500 RPM
Programmable operating temperature	Min. 4 °C – Max. 40 °C (+/-)6°C
Maximum rotor diameter	520 mm

Centrifuge rotors



Rotor 6 B

Rotor without bags



(R6B)

Max RPM	3500
Max RCF	4198
Capacity	6 Bucket



Bucket (set of 6)



(BU6)

Adapter (set of 6)



(ADA6B)

Maximum Bucket Capacity	1000 ml Blood Bag
Maximum Rotor Capacity	6 x 1000ml Blood bag



Fixed-Angle Rotor

(R6A)

Max RPM	7500
Max RCF	13376 x g
Capacity	1000 ml per unit
Adapter per Rotor	6

Optional accessories

Motorized gas spring



Designed for enhanced safety, the motorized gas springs enable smooth, controlled opening and closing of the centrifuge chamber, providing an additional layer of protection for the user.

Buffy Coat adapters



Includes specific adapters for Buffy Coat processing, optimizing cell separation and ensuring reliable, reproducible results. Ideal for clinical and research applications that require precise extraction of cellular components.



Barcode scanner



📞 11 2488 7703 ✉ presvac@presvac.net
🌐 presvac.net

